





















產品簡介

電阻體採用高能電子束焊接的錳銅合金材料，主要優點有：

1. 高精度、高強度、高穩定、高可靠；
2. 溫度係數小，熱電勢低；
3. 節約材料，降低能耗；
4. 結構緊湊，節約空間；
5. 電阻體全部採用來做測試電阻，發熱小，表面溫升高。

公司利用專有工藝技術，能生產極低阻值電阻。適用於電子式電度錶做取樣電阻。結構設計靈活，可按客戶要求進行設計。

分流器系列						
圖片	額定電流	額定電壓	阻值範圍	精度	溫標 (ppm/°C)	系列
	5A~150A	50mV/75mV/100mV/ 150mV	0.1mΩ~2 mΩ	0.5%, 1%	30/50	FLQ54
	5A~50A	50mV/75mV/100mV/ 150mV	0.5mΩ~3 mΩ	0.5%, 1%	30/50	FLQ54
	5A~150A	50mV/75mV/100mV/ 150mV	0.1mΩ~3 mΩ	1%	30/50	FLQ55
	5A~150A	50mV/75mV/100mV/ 150mV	0.1mΩ~3 mΩ	1%	30/50	FLQ55
	10A~150A	50mV/75mV/100mV/ 150mV	0.1mΩ~4 mΩ	1%	30/50	FLQ60
	5A~150A	50mV/75mV/100mV/ 150mV	0.1mΩ~4 mΩ	1%	30/50	FLQ60-1
	5A~150A	50mV/75mV/100mV/ 150mV	0.1mΩ~4 mΩ	1%	30/50	FLQ61
	5A~150A	50mV/75mV/100mV/ 150mV	0.1mΩ~4 mΩ	1%	30/50	FLQ61-1
	50A~500A	75mV	0.15mΩ~3 mΩ	0.5%, 1%	30/50	FL3
	50A~500A	75mV	0.15mΩ~3 mΩ	0.5%, 1%	30/50	FL3-1
	10A~1000A	10~100mV	0.05mΩ~3 mΩ	0.5%, 1%	50	汽車級低阻值 高精密電阻
		10~100mV	0.05mΩ~3 mΩ	0.5%, 1%	50	
		10~100mV	0.05mΩ~3 mΩ	0.5%, 1%	50	
		10~100mV	0.05mΩ~3 mΩ	0.5%, 1%	50	
		10~100mV	0.05mΩ~3 mΩ	0.5%, 1%		
	10A~75A	60mV/75mV/100mV	1 mΩ~10 mΩ	0.5%, 1%	30/50	FL2
	100A	75mV/100mV	0.75mΩ~1mΩ	0.5%, 1%	30/50	

分流器系列						
圖片	額定電流	額定電壓	阻值範圍	精度	溫標 (ppm/°C)	系列
	200A~2000A	75mV	0.375mΩ~1mΩ	0.5%,1%	30/50	FL-13
	5A~30A	50mV/75mV	1 mΩ~15 mΩ	0.2%,0.5%,1%	30/50	
	31A~50A	50mV/75mV	1mΩ~2mΩ	0.2%,0.5%,1%	30/50	
	51A~75A	75mV	0.5mΩ~2mΩ	0.2%,0.5%,1%	30/50	
	100A~300A	75mV	0.1mΩ~1mΩ	0.2%,0.5%,1%	30/50	
特殊阻值及尺寸可提供設計方案和定制						

聯繫我們

唐義儒 Miru

02-2719-3126

0926-701-811

Miru@goldsuntech.com.tw